

# FAST-TRACK 500

## FAST TRACK EMULSION

PRODUCT INFORMATION	
PRODUCT NAME	Fast-Track 500 Fast Track Emulsion (Interior and Exterior)
PRODUCT CODE	DI13
DESCRIPTION	Mr. Paint Man Fast-Track 500 Fast-Track Emulsion is a self-priming water-based acrylic emulsion paint specially formulated with an excellent breathable property to promote rapid release of moisture from newly plastered walls.
USAGE	Designed for use on interior and exterior masonry surface such as brickwork, plaster, cement panels and boards. It is suitable for use on both new and previously painted surfaces.
BENEFITS	Excellent for new renovation and project where you can fast track your painting works. It saves you time and money as the special features will reduce the number of coatings and you can now begin painting when the moisture content of the new plastered wall is <20%.
PACK SIZE	4.5L and 18 Litres.
COLOR RANGE	Refer to <b>Mr. Paint Man</b> Fast-Track 500 Colour Brochure.

PERFORMANCE GUIDE	
FILM PROPERTIES Water Resistance	Product will tolerate the atmospheric humidity levels present in normal exterior environment and will withstand moderate washing. Not suitable for use on immersed surfaces.
THEORETICAL COVERAGE	Approximately 10 - 12m <sup>2</sup> /litre
No. of Coats	2 or more for best result.

PRODUCT DATA	
COMPOSITION (nominal)	
Pigment	Lightfast Non-Lead Pigments and Mineral Extenders
Binder	Modified Acrylic Binder
Solvent	Water
VOLUME SOLID	39%

APPLICATION	
THINNING Brush or Roller	Ready for use. If dilution is required, add up to 5-10% clean water.

## Mr. Paint Man Fast-Track 500

Conventional Spray Airless Spray	Add up to 1 part of clean water to 10 parts of paint (10%). Ready to use.
SPRAY RECOMMENDATIONS Conventional Spray Airless Spray	Satisfactory through most equipment. A typical set up for airless spray application would be a minimum working pressure on paint of 140Kg/cm <sup>2</sup> (2000 lb/sq in) with a spray tip size 0.58mm (23 thou) and a spray tip angle of 65°.
Drying Times Touch Dry  Recoat CLEANING UP	Single coat at standard thickness : Surface dry in 10 min. (Dependant on temperature and humidity) 1 – 2 hours. Clean all equipment with clear water Immediately after use.

### PRE-APPLICATION

SURFACE PREPARATION AND SYSTEM INFORMATION	New wall must be allowed to cure and the moisture content should not exceed 20%. Ensure surfaces are sound, clean and free from contaminants and be thoroughly sand down using a suitable abrasive paper. When repainting, surfaces that remain powdery after cleaning must be primed with 1 coat of <b>Mr. Paint Man Powdery Wall Adhesion Promoter</b> . For selection of any non-standard colours, you may need to refer to Mr. Paint Man technical personnel to check on its colour sensitivity to alkalinity.
---	--

### PRECAUTION

SAFETY MEASURES AND INSTRUCTIONS	Keep container tightly closed. Keep out of reach of children. When applying paint, it is advisable to wear eye protection. In case of contact with eyes, rinse immediately with water and seek medical assistance. To remove splashes of paint from skin, use soap and water. In the event of spillage, contain and collect spillage using sand or soil. Do not empty into drains or water courses. Material Safety Data Sheet (MSDS) is available upon request.
-------------------------------------	---

For further details, kindly contact:

**MR. PAINT MAN SDN BHD** (649192-U)

No. A-30-06, 3-Two Square, No. 2 Jalan 19/1,  
46300 Petaling Jaya, Selangor Darul Ehsan, Malaysia.

Tel: 603 7960 8199 Fax: 603 7960 9399

As errors and omissions may occur, any advice, information, assistance provided by Mr. Paint Man Sdn Bhd regarding goods manufactured or their use or any application is not subject to any, expressed or implied, warranties.