

PRIMER SEALER

NEW WALL ALKALI RESISTANT SEALER

PRODUCT INFORMATION	
PRODUCT NAME	New Wall Alkali Resistant Primer Sealer
PRODUCT CODE	DI06
DESCRIPTION	Mr. Paint Man New Wall Alkali Resistant Primer Sealer is a premium grade, high performance water-based sealer.
USAGE	For use on new and preciously painted interior and exterior masonry surfaces such as brickwork, plaster, cement rendering and asbestos.
BENEFITS	Designed to protect the finish against chalking and efflorescence. Formulated with special acrylic resins, it will tolerate slightly damp surfaces.
PACK SIZE	4.5 and 18 Litres.
COLOR RANGE	White only.

PERFORMANCE GUIDE	
FILM PROPERTIES Water Resistance	Product will tolerate the atmospheric humidity levels present in normal interior and exterior environmental and will withstand moderate washing. Not suitable for use on immersed surfaces.
THEORETICAL COVERAGE	Approximately 10 - 12m ² /litre
No. of Coats	1 coat

PRODUCT DATA	
COMPOSITION (nominal) Pigment Binder Solvent	Lightfast Non-Lead Pigments and Mineral Extenders. Acrylic Emulsion. Water.
VOLUME SOLID	35

APPLICATION	
THINNING Brush or Roller	Ready for use. If dilution is required, add up to 5% clean water.
Conventional Spray Airless Spray	Add up to 1 part of clean water to 10 parts of paint (10%). Ready to use.

Mr. Paint Man PRIMER SEALER

SPRAY RECOMMENDATIONS Conventional Spray Airless Spray	Satisfactory through most equipment. A typical set up for airless spray application would be a minimum working pressure on paint of 140Kg/cm ² (2000 lb/sq in) with a spray tip size 0.38mm (15 thou) and a spray tip angle of 65°.
Drying Times Touch Dry Recoat	Single coat at standard thickness : Surface dry in 15 min (Dependant on temperature and humidity) 1 - 2 hours.
CLEANING UP	Clean all equipment with clear water immediately after use.

PRE-APPLICATION

SURFACE PREPARATION AND SYSTEM INFORMATION	Check for fungus and algae growth. If present, do a fungicidal wash (1 part household bleach with 3 parts water). Allow mixture to penetrate the surface. When dry, remove all fungi, algae, chalk or loosely adhering contaminants with a high pressure water-jetting machine. If after thoroughly preparation, surfaces remain powdery, it is highly recommended to prime with 1 coat of Mr. Paint Man 'Powdery Wall Adhesion Promoter' .
---	--

PRECAUTION

SAFETY MEASURES AND INSTRUCTIONS	Keep container tightly closed. Keep out of reach of children. When applying paint, it is advisable to wear eye protection. In case of contact with eyes, rinse immediately with water and seek medical assistance. To remove splashes of paint from skin, use soap and water. In the event of spillage, contain and collect spillage using sand or soil. Do not empty into drains or water courses. Chemical Safety Data Sheet (CSDS) is available upon request.
---	---

For further details, kindly contact:

MR. PAINT MAN SDN BHD (649192-U)

No. A-30-06, 3-Two Square, No. 2 Jalan 19/1,
46300 Petaling Jaya, Selangor Darul Ehsan, Malaysia.

Tel: 603 7960 8199 Fax: 603 7960 9399

As errors and omissions may occur, any advice, information, assistance provided by Mr. Paint Man Sdn Bhd regarding goods manufactured or their use or any application is not subject to any, expressed or implied, warranties.