

# PEARL MATT

## MATT FINISH FOR INTERIOR WALLS

PRODUCT INFORMATION	
PRODUCT NAME	Pearl Matt Easy Wash Emulsion Paint
PRODUCT CODE	D103 (Waterborne)
DESCRIPTION	<b>Mr. Paint Man</b> Pearl Matt Wall Finish is an elegant matt pearl finish for interior.
USAGE	For use on new or previously painted interior masonry surfaces such as brickwork, plaster and cement rendering.
BENEFITS	Formulated with a special emulsion, it is washable and maintains your walls elegant for longer.
PACK SIZE	0.9 and 4.5 Litres.
COLOR RANGE	Refer to <b>Mr. Paint Man</b> Emotion of Colours.

PERFORMANCE GUIDE	
FILM PROPERTIES Water Resistance	Product will tolerate the atmospheric humidity levels present in normal interior environment and will withstand moderate washing.
THEORETICAL COVERAGE	Approximately 10 - 12m <sup>2</sup> /litre
No. of Coat	2 or more for best result

PRODUCT DATA	
COMPOSITION (nominal)	
Pigment	Lightfast Non-Lead Pigments and Mineral Extenders.
Binder	PVA Copolymer Emulsion.
Solvent	Water.
VOLUME SOLID	35

APPLICATION	
THINNING	
Brush or Roller	For sealing new or bare surfaces thin with up to 1 part of clean water to 5 parts of paint (20%). For normal use, thinning is usually not necessary. If required, should not exceed 1 part of clean water to 10 parts of paint (10%).
Conventional Spray	Add up to 1 part of clean water to 5 parts of paint (20%).
Airless Spray	Ready for use.

Mr. Paint Man PEARL MATT

<b>SPRAY RECOMMENDATIONS</b> Conventional Spray Airless Spray	Satisfactory through most equipment. A typical set up for airless spray application would be a minimum working pressure on paint of 140Kg/cm <sup>2</sup> (2000 lb/sq in) with a spray tip size 0.58mm(23 thou) and a spray tip angle of 65°
<b>DRYING TIMES</b> Touch Dry  Recoat	Single coat at standard thickness : Surface dry in 30min. (Dependent on temperature and humidity) 1-2 hours.
<b>CLEANING UP</b>	Clean all equipment with clear water immediately after use.

**PRE-APPLICATION**

<b>SURFACE PREPARATION AND SYSTEM INFORMATION</b>	Repair all minor defects with suitable fillers. Ensure surfaces are dry, clean and free from contaminants. For new walls, apply 1 coat of <b>Mr. Paint Man 'New Wall Alkali Resistant Primer Sealer'</b> . When repainting, for surfaces that remain powdery after cleaning, apply 1 coat of <b>Mr. Paint Man 'Powdery Wall Adhesion Promoter'</b>
---	---

**PRECAUTION**

<b>SAFETY MEASURES AND INSTRUCTIONS</b>	Keep container tightly closed. Keep out of reach of children. When applying paint, it is advisable to wear eye protection. In case of contact with eyes, rinse immediately with water and seek medical assistance. To remove splashes of paint from skin, use soap and water. In the event of spillage, contain and collect spillage using sand or soil. Do not empty into drains or water courses. Chemical Safety Data Sheet (CSDS) is available upon request.
---	---

For further details, kindly contact:

**MR. PAINT MAN SDN BHD** (649192-U)  
No. A-30-06, 3-Two Square, No. 2 Jalan 19/1,  
46300 Petaling Jaya, Selangor Darul Ehsan, Malaysia.  
Tel: 603 7960 8199 Fax: 603 7960 9399

As errors and omissions may occur, any advice, information, assistance provided by Mr. Paint Man Sdn Bhd regarding goods manufactured or their use or any application is not subject to any, expressed or implied, warranties.