

# ADHESION PROMOTER

## POWDERY WALL

PRODUCT INFORMATION	
PRODUCT NAME	Powdery Wall Adhesion Promoter
PRODUCT CODE	DI07
DESCRIPTION	<b>Mr. Paint Man</b> Powdery Wall Adhesion Promoter is a premium high performance solvent-based primer.
USAGE	For protection on new or previously painted interior and exterior masonry surfaces such as brickwork, plaster, cement rendering and asbestos.
BENEFITS	Formulated with a special resin, it will form a seal over the powdery surface which reinforces the subsequent topcoat for a longer lasting finish.
PACK SIZE	4.5 and 18 Litres.
COLOR RANGE	White only.

PERFORMANCE GUIDE	
FILM PROPERTIES Water Resistance	Product will tolerate the atmospheric humidity levels present in normal interior and exterior environmental and will withstand moderate washing. Not suitable for use on immersed surfaces.
THEORETICAL COVERAGE	Approximately 13 - 15m <sup>2</sup> /litre
No. of Coats	1 coat

PRODUCT DATA	
COMPOSITION (nominal) Pigment Binder Solvent	Lightfast Non-Lead Pigments and Mineral Extenders. Vinyl-toluene acrylate co-polymer. White spirit.
VOLUME SOLID	45

APPLICATION	
THINNING Brush or Roller	For normal use, thinning is usually not necessary. If required, should not exceed 1 part of mineral turpentine to 10 parts of paint (10%).
Conventional Spray	Add up to 1 part of mineral turpentine to 10 parts of paint (10%).

## Mr. Paint Man ADHESION PROMOTER

Airless Spray	Ready to use.
<b>SPRAY RECOMMENDATIONS</b> Conventional Spray Airless Spray	Satisfactory through most equipment. A typical set up for airless spray application would be a minimum working pressure on paint of 140Kg/cm <sup>2</sup> (2000 lb/sq in) with a spray tip size 0.43mm(17 thou) and a spray tip angle of 65°.
Drying Times Touch Dry	Single coat at standard thickness : Surface dry in 1 hour (Dependant on temperature and humidity)
Recoat	2 - 3 hours.
<b>CLEANING UP</b>	Immediately with mineral turpentine.

### PRE-APPLICATION

<b>SURFACE PREPARATION AND SYSTEM INFORMATION</b>	Ensure surface to be painted is sound, clean, as dry as possible and free from grease, oil and wax. Check for fungus or algae growth and for powdery surface. If present, do a fungicidal wash (1 part household bleach with 3 parts water). Allow mixture to penetrate the surface. When dry, remove all fungi, algae, chalk or loosely adhering contaminants with a high pressure water-jetting machine.
---	--

### PRECAUTION

<b>SAFETY MEASURES AND INSTRUCTIONS</b>	Keep away from sources of ignition – no smoking. Keep away from food, drinks, animal feed and out of reach of children. If swallowed seek medical advice immediately. Container must be in a secure, upright position and be tightly closed and stored in a cool and shaded place. Work only in well ventilated areas. Do not breathe in vapour/spray. Avoid contact with skin. Wear eye/face protection. In case of eye contact, rinse immediately with plenty of water and seek medical advice. To remove splashes of paint from skin, use soap and water or a recognised cleanser. Do not empty into drains or water courses. Chemical Safety Data Sheet (CSDS) is available upon request.
---	---

For further details, kindly contact:

**MR. PAINT MAN SDN BHD** (649192-U)

No. A-30-06, 3-Two Square, No. 2 Jalan 19/1,  
46300 Petaling Jaya, Selangor Darul Ehsan, Malaysia.

Tel: 603 7960 8199 Fax: 603 7960 9399

As errors and omissions may occur, any advice, information, assistance provided by Mr. Paint Man Sdn Bhd regarding goods manufactured or their use or any application is not subject to any, expressed or implied, warranties.