

SUPERWASH HYGIENIC COATING

SPOT-LESS PEARL SHINE FINISH FOR INTERIOR

PRODUCT INFORMATION

PRODUCT NAME	Hygienic Antibacterial Wall Finish
PRODUCT CODE	D123 (Waterborne)
DESCRIPTION	Mr. Paint Man Anti-Bacteria Wall Finish is a tough and durable water-based coating that gives a luxurious pearl sheen finish for interior walls. Nano Silver is incorporated to inhibit bacterial growth thus promoting a more hygienic environment in your homes. Formulated with special emulsions, Superwash withstands regular cleaning with moderate disinfectants that controls flu virus.
USAGE	For new or previously painted interior masonry surfaces such as brickwork, plaster, ceiling and cement rendering.
BENEFITS	<ul style="list-style-type: none"> • Proven to kill 99.9% of bacteria within 24 hours. Bacteria such as MRSA, E-Coli and Staphylococcus Aureus is useful for inhibition of asthma, flu and diarrhoea. • Withstands regular cleaning with moderate disinfectants that controls flu virus. • High grade emulsion – last longer than ordinary emulsion
PACK SIZE	0.9 and 4.5 Litres.
COLOR RANGE	Refer to Mr. Paint Man Colour Catalog

PERFORMANCE GUIDE

FILM PROPERTIES Water Resistance	Product will tolerate the atmospheric humidity levels present in normal interior environment and will withstand moderate washing. Not suitable where heavy condensation is frequent, as in kitchens and bathrooms.
THEORETICAL COVERAGE No. of Coat	Approximately 10 - 12m ² /litre 2 or more for best result

PRODUCT DATA

COMPOSITION (nominal) Pigment Binder Solvent	Chalk resistant titanium dioxide and other high grade pigment Premium grade acrylic emulsion. Water.
---	--

Mr. Paint Man Superwash Hygienic Coating

APPLICATION	
THINNING Brush or Roller Conventional Spray Airless Spray	Ready for use. If dilution is required, add up to 5% clean water Dilution of up to 10% water Ready for use.
SPRAY RECOMMENDATIONS Conventional Spray Airless Spray	A typical set up would be a minimum atomising pressure of 2.8kg/cm ² and fluid pressure of 0.4kg/cm ³ with a nozzle size of 0.43mm. A typical set up would be a minimum 155kg/cm ³ with a nozzle size of 0.38-0.43mm and a spray tip angle of 65°
DRYING TIMES Touch Dry Recoat	Single coat at standard thickness : 10 mins dependant on temperature and humidity. 1-2 hours.
CLEANING UP	Clean all equipment with clear water immediately after use.

PRE-APPLICATION	
SURFACE PREPARATION AND SYSTEM INFORMATION	Repair all minor defects with suitable fillers. Ensure surfaces are dry, clean and free from contaminants. For new walls, apply 1 coat of Mr. Paint Man 'New Wall Alkali Resistant Primer Sealer' . When repainting, for surfaces that remain powdery after cleaning, apply 1 coat of Mr. Paint Man 'Powdery Wall Adhesion Promoter'

PRECAUTION	
SAFETY MEASURES AND INSTRUCTIONS	Keep container tightly closed. Keep out of reach of children. When applying paint, it is advisable to wear eye protection. In case of contact with eyes, rinse immediately with water and seek medical assistance. To remove splashes of paint from skin, use soap and water. In the event of spillage, contain and collect spillage using sand or soil. Do not empty into drains or water courses. Chemical Safety Data Sheet (CSDS) is available upon request.

For further details, kindly contact:

MR. PAINT MAN SDN BHD (649192-U)

No. A-30-06, 3-Two Square, No. 2 Jalan 19/1,
46300 Petaling Jaya, Selangor Darul Ehsan, Malaysia.

Tel: 603 7960 8199 Fax: 603 7960 9399

As errors and omissions may occur, any advice, information, assistance provided by Mr. Paint Man Sdn Bhd regarding goods manufactured or their use or any application is not subject to any, expressed or implied, warranties.