

TIMBALIKE

EXTERIOR NATURAL WOOD FINISH

PRODUCT INFORMATION	
PRODUCT NAME	Timbalike Exterior Natural Wood Finish
PRODUCT CODE	DI11
DESCRIPTION	Mr. Paint Man Timbalike Exterior Natural Wood Finish is a durable acrylic emulsion that has an opaque matt finishing.
USAGE	Designed for direct application to exterior wood surfaces including fences, fascias, exposed balconies, wood walls and cladding. This can also be applied direct onto galvanised iron such as gutters, downpipes, roof sheets and to primed metal surface.
BENEFITS	Contains light-fast pigments which give a colour fastness. Works as an effective mould control.
PACK SIZE	0.9 & 4.5 Litres.
COLOR RANGE	Refer to Mr. Paint Man Emotion of Colours.

PERFORMANCE GUIDE	
FILM PROPERTIES	
Water Resistance	Resistant to the atmospheric humidity levels normally experienced in exterior environment.
THEORETICAL COVERAGE	Approximately 10 - 11m ² /litre
No. of Coats	For best result, it is recommended to apply 3 coats.

PRODUCT DATA	
COMPOSITION (nominal)	
Pigment	Lightfast Non-Lead Pigments and Mineral Extenders.
Binder	Acrylic Emulsion.
Solvent	Water.
VOLUME SOLID	36

APPLICATION	
THINNING	
Brush or Roller	For normal use, thinning is usually not necessary. If required, should not exceed 1 part of clean water to 10 parts of paint (10%).
Conventional Spray	Add up to 1 part of clean water to 3 parts of paint (30%).
SPRAY RECOMMENDATIONS	

Mr. Paint Man TIMBALIKE

Conventional Spray	Satisfactory through most equipment.
Drying Times Touch Dry	Single coat at standard thickness : Surface dry in 10 min. (Dependant on temperature and humidity)
Recoat	2 - 3 hours.
CLEANING UP	Clean all equipment with clear water immediately after use.

PRE-APPLICATION

SURFACE PREPARATION AND SYSTEM INFORMATION	For new, unpainted wood, ensure surfaces are clean, thoroughly dry and free from grease, oil and wax. For repainting wood, thoroughly sand down using a suitable abrasive paper. Remove all rust, grease, wax and surface contaminants. On badly affected area, do a fungicidal wash (1 part household bleach with 3 parts water). Patch all holes and crevices with an appropriate wood filler before commence painting.
--	--

PRECAUTION

SAFETY MEASURES AND INSTRUCTIONS	Keep container tightly closed. Keep out of reach of children. When applying paint, it is advisable to wear eye protection. In case of contact with eyes, rinse immediately with water and seek medical assistance. To remove splashes of paint from skin, use soap and water. In the event of spillage, contain and collect spillage using sand or soil. Do not empty into drains or water courses. Chemical Safety Data Sheet (CSDS) is available upon request.
----------------------------------	---

For further details, kindly contact:

MR. PAINT MAN SDN BHD (649192-U)

No. A-30-06, 3-Two Square, No. 2 Jalan 19/1,
46300 Petaling Jaya, Selangor Darul Ehsan, Malaysia.

Tel: 603 7960 8199 Fax: 603 7960 9399

As errors and omissions may occur, any advice, information, assistance provided by Mr. Paint Man Sdn Bhd regarding goods manufactured or their use or any application is not subject to any, expressed or implied, warranties.