

# VICTOR 300

EMULSION

PRODUCT INFORMATION	
PRODUCT NAME	Victor 300 Emulsion
PRODUCT CODE	DI08
DESCRIPTION	<b>Mr. Paint Man</b> Victor 300 Emulsion is a fungus and algae resistant paint.
USAGE	Designed for use on all normal interior masonry surfaces such as brickwork, plaster, cement, asbestos and soft wallboards.
BENEFITS	Specially formulated to meet economical needs. Matt finish that smoothens surface imperfections.
PACK SIZE	7 and 18 Litres.
COLOR RANGE	White. Various colour available upon request

PERFORMANCE GUIDE	
FILM PROPERTIES Water Resistance	Product will tolerate the atmospheric humidity levels present in normal interior environment and will withstand moderate washing.
THEORETICAL COVERAGE	Approximately 10 - 12m <sup>2</sup> /litre
No. of Coats	2 or more for best result.

PRODUCT DATA	
COMPOSITION (nominal)	
Pigment	Lightfast Non-Lead Pigments and Mineral Extenders.
Binder	PVA Emulsion.
Solvent	Water.
VOLUME SOLID	39

APPLICATION	
THINNING	
Brush or Roller	Ready for use. If dilution is required, add up to 5% clean water.
Conventional Spray	Add up to 1 part of clean water to 3 parts of paint (30%).
Airless Spray	Ready to use.

Mr. Paint Man VICTOR 300

<b>SPRAY RECOMMENDATIONS</b> Conventional Spray Airless Spray	Satisfactory through most equipment. A typical set up for airless spray application would be a minimum working pressure on paint of 140Kg/cm <sup>2</sup> (2000 lb/sq in) with a spray tip size 0.58mm (23 thou) and a spray tip angle of 65°.
Drying Times Touch Dry  Recoat	Single coat at standard thickness : Surface dry in 10 min. (Dependant on temperature and humidity) 1 – 2 hours.
<b>CLEANING UP</b>	Clean all equipment with clear water Immediately after use.

**PRE-APPLICATION**

<b>SURFACE PREPARATION AND SYSTEM INFORMATION</b>	Ensure surfaces are dry, clean and free from contaminants and be thoroughly sand down using a suitable abrasive paper. When repainting, surfaces that remain powdery after cleaning must be primed with 1 coat of <b>Mr. Paint Man 'Powdery Wall Adhesion Promoter'</b> .
---	--

**PRECAUTION**

<b>SAFETY MEASURES AND INSTRUCTIONS</b>	Keep container tightly closed. Keep out of reach of children. When applying paint, it is advisable to wear eye protection. In case of contact with eyes, rinse immediately with water and seek medical assistance. To remove splashes of paint from skin, use soap and water. In the event of spillage, contain and collect spillage using sand or soil. Do not empty into drains or water courses. Chemical Safety Data Sheet (CSDS) is available upon request.
---	---

For further details, kindly contact:

**MR. PAINT MAN SDN BHD** (649192-U)  
No. A-30-06, 3-Two Square, No. 2 Jalan 19/1,  
46300 Petaling Jaya, Selangor Darul Ehsan, Malaysia.  
Tel: 603 7960 8199      Fax: 603 7960 9399

As errors and omissions may occur, any advice, information, assistance provided by Mr. Paint Man Sdn Bhd regarding goods manufactured or their use or any application is not subject to any, expressed or implied, warranties.