

WEATHER PAINT

ACRYLIC EXTERIOR WALL FINISH

PRODUCT INFORMATION	
PRODUCT NAME	Weather Paint Acrylic Exterior Wall Finish
PRODUCT CODE	D101 (Waterborne)
DESCRIPTION	Mr. Paint Man Weather Paint Acrylic Exterior Wall Finish is a premium quality, 100% acrylic water based emulsion paint.
USAGE	For protection on new or previously painted exterior masonry surfaces such as brickwork, plaster, cement rendering, and asbestos.
BENEFITS	Formulated to give 5.5 years protection to exterior walls against flaking, peeling, excessive colour fading, fungi and algae attack.
PACK SIZE	4.5 and 18 Litres.
COLOR RANGE	Refer to Mr. Paint Man Emotion of Colours.

PERFORMANCE GUIDE	
FILM PROPERTIES	
Chemical Resistance	Resistant to mild atmospheric fume attack and to the salts in the new mortar, cement rendering and similar surfaces.
Water Resistance	Resistant to the atmospheric humidity levels normally experienced in exterior environment.
THEORETICAL COVERAGE	Approximately 10 - 12m ² /litre.
No. of Coat	2 or more for best result

PRODUCT DATA	
COMPOSITION (nominal)	
Pigment	Lightfast Non-Lead Pigments and Mineral Extenders.
Binder	Acrylic Emulsion.
Solvent	Water.

APPLICATION	
THINNING	
Brush or Roller	For sealing new or bare surfaces, thin with up to 1 part of clean water to 10 parts of paint (10%) For normal use, thinning is usually not necessary.
Conventional Spray Airless Spray	Add up to 1 part of clean water to 3 parts of paint (30%). Ready for use. Thinning is usually not required.

Mr. Paint Man WEATHER PAINT

SPRAY RECOMMENDATIONS Conventional Spray Airless Spray	Satisfactory through most equipment. A typical set up for airless spray application would be a minimum working pressure on paint of 140Kg/cm ² (2000 lb/sq in) with a spray tip size 0.58mm (23 thou) and a spray tip angle of 65°
DRYING TIMES Touch Dry Recoat	Single coat at standard thickness : Dependant on temperature and humidity. 1-2 hours.
CLEANING UP	Clean all equipment with clean water immediately after use.

PRE-APPLICATION

SURFACE PREPARATION AND SYSTEM INFORMATION	Check for fungus and algae growth. If present, do a fungicidal wash (1 part household bleach: 3 parts water). Allow mixture to penetrate the surface. When dry, remove all fungi, algae, chalk or loosely adhering contaminants with a high pressure water-jetting machine .Wall must be thoroughly dry before painting. To achieve better results for new walls, it is highly recommended to prime the cleaned surface with 1 coat of Mr. Paint Man 'New Wall Alkali Resistant Primer Sealer' . When repainting, surfaces that remain powdery after cleaning must be primed with 1 coat of Mr. Paint Man 'Powdery Wall Adhesion Promoter'
---	---

PRECAUTION

SAFETY MEASURES AND INSTRUCTIONS	Keep container tightly closed. Keep out of reach of children. When applying paint, it is advisable to wear eye protection. In case of contact with eyes, rinse immediately with water and seek medical assistance. To remove splashes of paint from skin, use soap and water. In the event of spillage, contain and collect spillage using sand or soil. Do not empty into drains or water courses. Chemical Safety Data Sheet (CSDS) is available upon request.
---	---

For further details, kindly contact:

MR. PAINT MAN SDN BHD (649192-U)
No. A-30-06, 3-Two Square, No. 2 Jalan 19/1,
46300 Petaling Jaya, Selangor Darul Ehsan, Malaysia.
Tel: 603 7960 8199 Fax: 603 7960 9399

As errors and omissions may occur, any advice, information, assistance provided by Mr. Paint Man Sdn Bhd regarding goods manufactured or their use or any application is not subject to any, expressed or implied, warranties