

# WOODSCREEN INTERIOR AND EXTERIOR TRANSPARENT WOOD FINISH

PRODUCT INFORMATION	
PRODUCT NAME	Woodscreen Exterior And Interior Transparent Wood Finish
PRODUCT CODE	DI12
DESCRIPTION	<b>Mr. Paint Man</b> Woodscreen Exterior And Interior Transparent Wood Finish is a solvent based wood finish.
USAGE	Designed for use as a decorative wood stain on all types of new or previously painted wood surfaces.
BENEFITS	Formulated with a special resin to provide long lasting protection and also acts as a protection that filters out UV rays, minimizing the traditional problems of cracking, flaking and peeling.
PACK SIZE	0.9L and 4.5 Litres.
COLOR RANGE	Refer to Mr. Paint Man Emotion of Colours.

PERFORMANCE GUIDE	
FILM PROPERTIES	
Chemical Resistance	Resistant to mild chemical fume attack but where there is heavy attack, e.g. actual contact with chemicals, specialist paint systems will be required.
Heat Resistance	Generally resistant to heat up to 90°C, but some discolouration of light colours may occur at temperatures above 80°C.
Water Resistance	Resistant to the atmospheric humidity levels present in normal interior and exterior environments and will withstand repeated washing. Not suitable for use on immersed surfaces.
THEORETICAL COVERAGE	Approximately 12 - 14m <sup>2</sup> /litre
No. of Coats	For best result, it is recommended to apply 3 coats

PRODUCT DATA	
COMPOSITION (nominal)	
Pigment	Lightfast Non-Lead Pigments.
Binder	Modified & Polyurethane Alkyd.
Solvent	White Spirit.
VOLUME SOLID	50

APPLICATION	
THINNING Brush or Roller	For normal use, thinning is usually not necessary. If required, should not exceed 1 part of mineral turpentine to 5 parts of paint (20%).
Drying Times Touch Dry	Single coat at standard thickness : Surface dry in 1-2 hours (Dependant on temperature and humidity)
Recoat CLEANING UP	1 - 2 hours. Immediately with mineral turpentine.

PRE-APPLICATION	
SURFACE PREPARATION AND SYSTEM INFORMATION	Ensure surfaces are dry, clean and free from contaminants and thoroughly sand down using a suitable abrasive paper and dust off. Patch all holes and crevices with an appropriate wood filler before commence painting.

PRECAUTION	
SAFETY MEASURES AND INSTRUCTIONS	Keep away from sources of ignition – no smoking. Keep away from food, drinks, animal feed and out of reach of children. If swallowed seek medical advice immediately. Container must be in a secure, upright position and be tightly closed and stored in a cool and shaded place. Work only in well ventilated areas. Do not breathe in vapour/spray. Avoid contact with skin. Wear eye/face protection. In case of eye contact, rinse immediately with plenty of water and seek medical advice. To remove splashes of paint from skin, use soap and water or a recognised cleanser. Do not empty into drains or water courses. Chemical Safety Data Sheet (CSDS) is available upon request.

For further details, kindly contact:

**MR. PAINT MAN SDN BHD** (649192-U)

No. A-30-06, 3-Two Square, No. 2 Jalan 19/1,  
46300 Petaling Jaya, Selangor Darul Ehsan, Malaysia.

Tel: 603 7960 8199 Fax: 603 7960 9399

As errors and omissions may occur, any advice, information, assistance provided by Mr. Paint Man Sdn Bhd regarding goods manufactured or their use or any application is not subject to any, expressed or implied, warranties.