

EASY WASH

MATT FINISH FOR INTERIOR WALLS

PRODUCT INFORMATION	
PRODUCT NAME	Mr.Paint Man Easy Wash
PRODUCT CODE	DI28 (Waterborne)
DESCRIPTION	Mr. Paint Man Easy Wash Wall Finish is a premium eco-friendly paint that gives a durable, smooth and luxurious matte finish for interior walls.
USAGE	For use on new or previously painted interior masonry surfaces such as brickwork, plaster and cement rendering.
BENEFITS	Formulated with a special emulsion for easy cleaning, common household stains can be wiped off without damaging the paint film. This Easy-to-clean feature will maintain your walls elegance for longer.
PACK SIZE	0.9 Litres, 4.5 Litres & 18 Litres
COLOR RANGE	Refer to Mr. Paint Man Emotion of Colours.

PERFORMANCE GUIDE	
FILM PROPERTIES Water Resistance	Product will tolerate the atmospheric humidity levels present in normal interior environment and will withstand moderate washing.
THEORETICAL COVERAGE	Approximately 10 - 12m ² /litre
No. of Coat	2 or more for best result

PRODUCT DATA	
COMPOSITION (nominal) Pigment Binder Solvent	Lightfast Non-Lead Pigments and Mineral Extenders. PVA Copolymer Emulsion. Water.
VOLUME SOLID	35

APPLICATION	
THINNING Brush or Roller	For sealing new or bare surfaces thin with up to 1 part of clean water to 5 parts of paint (20%). For normal use, thinning is usually not necessary. If required, should not exceed 1 part of clean water to 10 parts of paint (10%).
Conventional Spray Airless Spray	Add up to 1 part of clean water to 5 parts of paint (20%). Ready for use.

Mr. Paint Man Easy Wash

SPRAY RECOMMENDATIONS Conventional Spray Airless Spray	Satisfactory through most equipment. A typical set up for airless spray application would be a minimum working pressure on paint of 140Kg/cm ² (2000 lb/sq in) with a spray tip size 0.58mm(23 thou) and a spray tip angle of 65°
DRYING TIMES Touch Dry Recoat	Single coat at standard thickness : Surface dry in 30min. (Dependent on temperature and humidity) 1-2 hours.
CLEANING UP	Clean all equipment with clear water immediately after use.

PRE-APPLICATION

SURFACE PREPARATION AND SYSTEM INFORMATION	Repair all minor defects with suitable fillers. Ensure surfaces are dry, clean and free from contaminants. For new walls, apply 1 coat of Mr. Paint Man 'New Wall Alkali Resistant Primer Sealer' . When repainting, for surfaces that remain powdery after cleaning, apply 1 coat of Mr. Paint Man 'Powdery Wall Adhesion Promoter'
---------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

PRECAUTION

SAFETY MEASURES AND INSTRUCTIONS	Keep container tightly closed. Keep out of reach of children. When applying paint, it is advisable to wear eye protection. In case of contact with eyes, rinse immediately with water and seek medical assistance. To remove splashes of paint from skin, use soap and water. In the event of spillage, contain and collect spillage using sand or soil. Do not empty into drains or water courses. Safety Data Sheet (SDS) is available upon request.
-----------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

For further details, kindly contact:

MR. PAINT MAN SDN BHD (649192-U)

No. A-30-06, 3-Two Square, No. 2 Jalan 19/1,
46300 Petaling Jaya, Selangor Darul Ehsan, Malaysia.

Tel: 603 7960 8199 Fax: 603 7960 9399

As errors and omissions may occur, any advice, information, assistance provided by Mr. Paint Man Sdn Bhd regarding goods manufactured or their use or any application is not subject to any, expressed or implied, warranties.