

WEATHER PAINT TRADE

EXTERIOR PAINT

PRODUCT INFORMATION	
PRODUCT NAME	MR. PAINT MAN WEATHER PAINT TRADE
PRODUCT CODE	DI30
DESCRIPTION	Mr. Paint Man WEATHER PAINT TRADE is a quality acrylic-based emulsion paint specially formulated with a durable paint film to provide protection against weather attack.
USAGE	Designed for use on interior and exterior masonry surface such as brickwork, plaster, cement panels and boards. It is suitable for use on both new and previously painted surfaces.
BENEFITS	Formulated to provide the ultimate performance to protect your home against harsh weather conditions, dirt & fungus. It has excellent adhesion on all types of exterior wall surfaces.
PACK SIZE	5L and 20 Litres.
COLOR RANGE	Refer to Mr. Paint Man Weather Paint Trade Colour Brochure.

PERFORMANCE GUIDE	
FILM PROPERTIES Water Resistance	Product will tolerate the atmospheric humidity levels present in normal exterior environment and will withstand moderate washing. Not suitable for use on immersed surfaces.
THEORETICAL COVERAGE	Approximately 10 - 12m ² /litre
No. of Coats	2 or more for best result.

PRODUCT DATA	
COMPOSITION (nominal)	
Pigment	Lightfast Non-Lead Pigments and Mineral Extenders
Binder	Modified Acrylic Binder
Solvent	Water
VOLUME SOLID	39%

APPLICATION	
THINNING	
Brush or Roller	Ready for use. If dilution is required, add up to 5-10% clean water.
Conventional Spray	Add up to 1 part of clean water to 10 parts of paint (10%).

Airless Spray	Ready to use.
SPRAY RECOMMENDATIONS Conventional Spray Airless Spray	Satisfactory through most equipment. A typical set up for airless spray application would be a minimum working pressure on paint of 140Kg/cm ² (2000 lb/sq in) with a spray tip size 0.58mm (23 thou) and a spray tip angle of 65°.
Drying Times Touch Dry	Single coat at standard thickness : Surface dry in 10 min. (Dependant on temperature and humidity)
Recoat	1 – 2 hours.
CLEANING UP	Clean all equipment with clear water Immediately after use.

PRE-APPLICATION

SURFACE PREPARATION AND SYSTEM INFORMATION	New wall must be allowed to cure and the moisture content should not exceed 20%. Ensure surfaces are sound, clean and free from contaminants and be thoroughly sand down using a suitable abrasive paper. When repainting, surfaces that remain powdery after cleaning must be primed with 1 coat of Mr. Paint Man Powdery Wall Adhesion Promoter . For selection of any non-standard colours, you may need to refer to Mr. Paint Man technical personnel to check on its colour sensitivity to alkalinity.
---	--

PRECAUTION

SAFETY MEASURES AND INSTRUCTIONS	Keep container tightly closed. Keep out of reach of children. When applying paint, it is advisable to wear eye protection. In case of contact with eyes, rinse immediately with water and seek medical assistance. To remove splashes of paint from skin, use soap and water. In the event of spillage, contain and collect spillage using sand or soil. Do not empty into drains or water courses. Safety Data Sheet (SDS) is available upon request.
---	---

For further details, kindly contact:

MR. PAINT MAN SDN BHD (649192-U)

No. A-30-06, 3-Two Square, No. 2 Jalan 19/1,
46300 Petaling Jaya, Selangor Darul Ehsan, Malaysia.

Tel: 603 7960 8199 Fax: 603 7960 9399

As errors and omissions may occur, any advice, information, assistance provided by Mr. Paint Man Sdn Bhd regarding goods manufactured or their use or any application is not subject to any, expressed or implied, warranties.